Printing date 22.09.2015 Version number 1 Revision: 22.09.2015

# SECTION 1: Identification of the substance/mixture and of the company undertaking

Protective coatings

· 1.1 Product identifier

Trade name: CO.26 ZP-Coating HB

· Article number: Z5010448KL0200

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Shipcoat BV Industrieweg 17 2995 BE Heerjansdam Nederland Tel: +31 (0)78 677 11 88

e-mail: administratie@shipcoat.nl

Further information obtainable from:

R&D department

Product Safety Department

· 1.4 Emergency telephone number:

NVIC: +31(030) 2748888

Only for the purpose of informing medical personnel in cases of acute intoxications. Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen.

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

Printing date 22.09.2015 Version number 1 Revision: 22.09.2015

Trade name: CO.26 ZP-Coating HB

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information:

Contains 2-butanone oxime. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Resin mixture

· Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene  Flam. Liq. 3, H226;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-<50%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate → Flam. Liq. 3, H226	1-<2,5%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0 Reg.nr.: 01-2119539477-28	2-butanone oxime  © Carc. 2, H351; © Eye Dam. 1, H318; © Acute Tox. 4, H312; Skin Sens. 1, H317	.15-0,25%

· Additional information: For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)

Printing date 22.09.2015 Version number 1 Revision: 22.09.2015

Trade name: CO.26 ZP-Coating HB

(Contd. of page 2)

5.3 Advice for firefighters

· Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

# Ingredients with limit values that require monitoring at the workplace: 1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m<sup>3</sup>, 50 ppm

Skin

#### 108-65-6 2-methoxy-1-methylethyl acetate

IOELV Short-term value: 550 mg/m3, 100 ppm

Long-term value: 275 mg/m³, 50 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection: Not required.

(Contd. on page 4)

(Contd. of page 3)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.09.2015 Version number 1 Revision: 22.09.2015

Trade name: CO.26 ZP-Coating HB

#### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

# SECTION 9: Physical and chemical properties

<ul> <li>9.1 Information on basic physical</li> <li>General Information</li> <li>Appearance:</li> </ul>	and chemical properties
Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Oddar tillesildia.	
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	137 ℃
· Flash point:	30 ℃
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	500 ℃
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive
	air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1,1 Vol %
Upper:	7,0 Vol %
· Vapour pressure at 20 °C:	6,7 hPa
· Density at 20 ℃:	1,132 g/cm³

(Contd. on page 5)

Printing date 22.09.2015 Version number 1 Revision: 22.09.2015

Trade name: CO.26 ZP-Coating HB

		(Contd. of page
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/	water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic at 20 ℃:	100 s (ISO 6 mm)	
Solvent content:		
Organic solvents:	40,9 %	
VÕC (EC)	40,90 %	
Solids content:	58,9 %	
9.2 Other information	No further relevant information available.	

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

LD/LC50 value	e relevant for	classification
LD/LUJU Value	s i cicvaiil iui	Giassilication.

## 1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)
Dermal LD50 2000 mg/kg (rabbit)

- Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

# SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 6)

Printing date 22.09.2015 Version number 1 Revision: 22.09.2015

Trade name: CO.26 ZP-Coating HB

(Contd. of page 5)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR,RID,ADN, ADN, IMDG	Void
IATA	UN1263
14.2 UN proper shipping name ADR,RID,ADN, ADN, IMDG	Void
IATA	PAINT
14.3 Transport hazard class(es)	
ADR,RID,ADN, IMDG	
Class	Void
ADN	
ADN/R Class:	Void -
IATA	
3	O Elegenesis la limitata
Class	3 FIAMMANIA IINI IINS
Class Label	3 Flammable liquids. 3
Label 14.4 Packing group	3
Label 14.4 Packing group ADR,RID,ADN, IMDG	Void
Label 14.4 Packing group ADR,RID,ADN, IMDG IATA	Void
Label 14.4 Packing group ADR,RID,ADN, IMDG	Void
Label 14.4 Packing group ADR,RID,ADN, IMDG IATA	Void

(Contd. of page 6)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.09.2015 Version number 1 Revision: 22.09.2015

Trade name: CO.26 ZP-Coating HB

· Transport/Additional information:

· ADR/RID/ADN

· Remarks: > 450 l: 3 F1, III

· IMDG

· Remarks: > 30 I: 3, III

Void UN "Model Regulation":

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment. P241

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

- · Department issuing MSDS: product safety department
- · Contact: Tel: +31 (0)78 677 11 88

(Contd. on page 8)

Version number 1 Revision: 22.09.2015 Printing date 22.09.2015

Trade name: CO.26 ZP-Coating HB

(Contd. of page 7)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2