

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2019

Version number 35

Revision: 31.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· Trade name: **CO.601 Synth. lakverf hooggl. NT**

SHIPCOAT® B.V.
Protective coatings

· Article number: **A5012851NT050**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Application of the substance / the mixture** Paint

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Shipcoat BV
Industrieweg 17
2995 BE Heerjansdam
Nederland
Tel: +31 (0)78 677 11 88
e-mail: administratie@shipcoat.nl

· **Further information obtainable from:**

R&D department
Product Safety Department

· **1.4 Emergency telephone number:**

NVIC: +31(030) 2748888

Only for the purpose of informing medical personnel in cases of acute intoxications.

Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen.

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS08

· **Signal word** Warning

· **Hazard-determining components of labelling:**

Naphtha (petroleum), hydrodesulfurized heavy

· **Hazard statements**

H226 Flammable liquid and vapour.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2019

Version number 35

Revision: 31.07.2019

Trade name: CO.601 Synth. lakverf hooggl. NT

(Contd. of page 1)

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P241 Use explosion-proof electrical/ventilating/lighting equipment.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains 2-butanone oxime, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures
Description: Resin mixture

Dangerous components:

CAS: 64742-48-9 EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39	Naphtha (petroleum), hydrotreated heavy, content benzene 0,1% ⚠ Asp. Tox. 1, H304	25-<50%
CAS: 64742-82-1 EINECS: 265-185-4 Index number: 649-330-00-2	Naphtha (petroleum), hydrodesulfurized heavy ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; Asp. Tox. 1, H304	7-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	1-<2.5%
CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-<2.5%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0 Reg.nr.: 01-2119539477-28	2-butanone oxime ⚠ Carc. 2, H351; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317	0.5-<1%
CAS: 136-52-7 EINECS: 205-250-6	cobalt bis(2-ethylhexanoate) ⚠ Repr. 2, H361f; ⚠ Aquatic Acute 1, H400; ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	0.25-0.5%
CAS: 22464-99-9 EINECS: 245-018-1	Zirconium carboxylaat ⚠ Repr. 2, H361d	0.15-0.25%

Additional information: For the wording of the listed hazard phrases refer to section 16.

EU

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2019

Version number 35

Revision: 31.07.2019

Trade name: CO.601 Synth. lakverf hooggl. NT

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment:

No special measures required.

Mouth respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

No special measures required.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2019

Version number 35

Revision: 31.07.2019

Trade name: CO.601 Synth. lakverf hooggl. NT

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

108-65-6 2-methoxy-1-methylethyl acetate

IOELV	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
-------	--

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

EU

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2019

Version number 35

Revision: 31.07.2019

Trade name: CO.601 Synth. lakverf hooggl. NT

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	142 °C

Flash point: 39 °C

Flammability (solid, gas): Not applicable.

Ignition temperature: 240 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:	0.6 Vol %
Upper:	7 Vol %

Vapour pressure at 20 °C: 1 hPa

Density at 20 °C: 0.80786 g/cm³

Relative density: Not determined.

Vapour density: Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic:	Not determined.
Kinematic at 20 °C:	100 s (ISO 6 mm)

Solvent content:

Organic solvents:	43.1 %
VOC (EC)	43.11 %

Solids content: 59.8 %

9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity: No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions: No dangerous reactions known.

10.4 Conditions to avoid: No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2019

Version number 35

Revision: 31.07.2019

Trade name: CO.601 Synth. lakverf hooggl. NT

(Contd. of page 5)

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**· **Acute toxicity** Based on available data, the classification criteria are not met.· **LD/LC50 values relevant for classification:**

64742-48-9 Naphtha (petroleum), hydrotreated heavy, content benzene 0,1%

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >3,000 mg/kg (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)

Dermal LD50 >3,400 mg/kg (rat)

Inhalative LC50/4 h >10.2 mg/l (rat)

96-29-7 2-butanone oxime

Oral LD50 3,700 mg/kg (rat)

Dermal LD50 200-2,000 mg/kg (rat)

Inhalative LC50/4 h 20 mg/l (rat)

· **Primary irritant effect:**· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.· **Carcinogenicity** Based on available data, the classification criteria are not met.· **Reproductive toxicity** Based on available data, the classification criteria are not met.· **STOT-single exposure** Based on available data, the classification criteria are not met.· **STOT-repeated exposure**

May cause damage to the central nervous system through prolonged or repeated exposure.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**· **Aquatic toxicity:** No further relevant information available.· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.

EU

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.07.2019

Version number 35

Revision: 31.07.2019

Trade name: CO.601 Synth. lakverf hooggl. NT

(Contd. of page 6)

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information**14.1 UN-Number****ADR/RID/ADN, ADN, IMDG**

Void

IATA

UN1263

14.2 UN proper shipping name**ADR/RID/ADN, ADN, IMDG**

Void

IATA

PAINT

14.3 Transport hazard class(es)**ADR/RID/ADN, IMDG****Class**

Void

ADN**ADN/R Class:**

Void

-

IATA**Class**

3 Flammable liquids.

Label

3

14.4 Packing group**ADR/RID/ADN, IMDG**

Void

IATA

III

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

Transport/Additional information:**ADR/RID/ADN****Remarks:**

> 450 l: 3 F1, III

IMDG**Remarks:**

> 30 l: 3, III

UN "Model Regulation":

Void

EU

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.07.2019

Version number 35

Revision: 31.07.2019

Trade name: CO.601 Synth. lakverf hooggl. NT

(Contd. of page 7)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Naphtha (petroleum), hydrodesulfurized heavy
- **Hazard statements**
H226 Flammable liquid and vapour.
H373 May cause damage to the central nervous system through prolonged or repeated exposure.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.07.2019

Version number 35

Revision: 31.07.2019

Trade name: CO.601 Synth. lakverf hooggl. NT

(Contd. of page 8)

H361f Suspected of damaging fertility.
 H372 Causes damage to the central nervous system through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** product safety department

· **Contact:** Tel: +31 (0)78 677 11 88

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * **Data compared to the previous version altered.**

EU