

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 280

Revision: 19.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· Trade name: **Epoxy Universal Primer HB 16.76 grijs**

SHIPCOAT® B.V.
Protective coatings

· Article number: E501644100200

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Application of the substance / the mixture** Paint

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Shipcoat BV
Industrieweg 17
2995 BE Heerjansdam
Nederland
Tel: +31 (0)78 677 11 88
e-mail: administratie@shipcoat.nl

· **Further information obtainable from:**

Product Safety Department
R&D department

· **1.4 Emergency telephone number:**

NVIC: +31(030) 2748888

Only for the purpose of informing medical personnel in cases of acute intoxications.

Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen.

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**

phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]

Phenol, methylstyrenated

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 280

Revision: 19.02.2020

Trade name: Epoxy Universal Primer HB 16.76 grijs

(Contd. of page 1)

bis[4-(2,3-epoxypropoxy)phenyl]propane

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures
Description: Resin mixture

Dangerous components:

CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO ₂) substance with a Community workplace exposure limit	25-<50%
CAS: 25036-25-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'- [(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane] ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-<15%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-<15%
CAS: 68512-30-1 EC number: 700-960-7	Phenol, methylstyrenated ⚠ Skin Sens. 1, H317; Aquatic Chronic 3, H412	5-<7%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22	oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	1-<2.5%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	1-<2.5%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 3, H331; ⚠ STOT SE 3, H336	0.5-<1%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 280

Revision: 19.02.2020

Trade name: Epoxy Universal Primer HB 16.76 grijs

CAS: 1675-54-3

EINECS: 216-823-5

Index number: 603-073-00-2

bis[4-(2,3-epoxypropoxy)phenyl]propane

⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317

(Contd. of page 2)

0.15-0.25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

· 5.3 Advice for firefighters

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

No special measures required.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 280

Revision: 19.02.2020

Trade name: Epoxy Universal Primer HB 16.76 grijs

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 14808-60-7 Quartz (SiO₂)

BOELV	Long-term value: 0.1* mg/m ³ *respirable fraction
-------	---

CAS: 1330-20-7 xylene

IOELV	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
-------	--

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

IOELV	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
-------	--

CAS: 107-98-2 1-methoxy-2-propanol

IOELV	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Skin
-------	---

- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 280

Revision: 19.02.2020

Trade name: Epoxy Universal Primer HB 16.76 grijs

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties
· General Information
· Appearance:

Form: Fluid
Colour: According to product specification

· Odour: Characteristic

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 137-143 °C

· Flash point: 30 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 500 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.1 Vol %

Upper: 7 Vol %

· Vapour pressure at 20 °C: 6.7-8.2 hPa

· Density at 20 °C: 1.595 g/cm³

· Relative density Not determined.

· Vapour density Not determined.

· Evaporation rate Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic at 20 °C: 100 s (ISO 6 mm)

· Solvent content:

Organic solvents: 18.9 %

VOC (EC) 18.94 %

Solids content: 81.7 %

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 280

Revision: 19.02.2020

Trade name: Epoxy Universal Primer HB 16.76 grijs

(Contd. of page 5)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

CAS: 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 280

Revision: 19.02.2020

Trade name: Epoxy Universal Primer HB 16.76 grijs


(Contd. of page 6)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR/RID/ADN, ADN, IMDG · IATA | <p style="text-align: center;">Void</p> <p style="text-align: center;">UN1263</p> |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR/RID/ADN, ADN, IMDG · IATA | <p style="text-align: center;">Void</p> <p style="text-align: center;">PAINT</p> |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR/RID/ADN, IMDG · Class | <p style="text-align: center;">Void</p> |
| <ul style="list-style-type: none"> · ADN · ADN/R Class: | <p style="text-align: center;">Void</p> <p style="text-align: center;">-</p> |
| <ul style="list-style-type: none"> · IATA | |
| <div style="text-align: center;">  </div> | |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: center;">3 Flammable liquids.</p> <p style="text-align: center;">3</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR/RID/ADN, IMDG · IATA | <p style="text-align: center;">Void</p> <p style="text-align: center;">III</p> |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: | <p style="text-align: center;">Not applicable.</p> |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user | <p style="text-align: center;">Not applicable.</p> |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | <p style="text-align: center;">Not applicable.</p> |
| <ul style="list-style-type: none"> · Transport/Additional information: | |
| <ul style="list-style-type: none"> · ADR/RID/ADN · Remarks: | <p style="text-align: center;">> 450 l: 3 F1, III</p> |
| <ul style="list-style-type: none"> · IMDG · Remarks: | <p style="text-align: center;">> 30 l: 3, III</p> |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 280

Revision: 19.02.2020

Trade name: Epoxy Universal Primer HB 16.76 grijs

(Contd. of page 7)

UN "Model Regulation": Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]
Phenol, methylstyrenated
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
bis[4-(2,3-epoxypropoxy)phenyl]propane
- **Hazard statements**
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 280

Revision: 19.02.2020

Trade name: Epoxy Universal Primer HB 16.76 grijs

(Contd. of page 8)

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** product safety department

· **Contact:** Tel: +31 (0)78 677 11 88

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * **Data compared to the previous version altered.**

EU